

Serial No. 09/760,017
60130-984
OOMRA0174

AMENDMENT

IN THE CLAIMS:

1. (CURRENTLY AMENDED) A motorized reduction gear comprising:
a rotor provided with a rotor shaft bearing a commutator;
said commutator including a body having an inner surface mounted on said rotor shaft and
an opposing outer surface;~~and~~
a reduction gearbox containing a gearwheel engaged with a worm of said rotor shaft; and
a magnetic ring mounted on said rotor shaft ~~in order so~~ that a number of rotations of said
rotor shaft can be counted, ~~and~~ wherein said magnetic ring is attached on said opposing outer
surface of said body of said commutator.
2. (PREVIOUSLY PRESENTED) The motorized reduction gear as recited in Claim 1,
wherein said magnetic ring is overmolded on said body of said commutator.
3. (CURRENTLY AMENDED) The motorized reduction gear as recited in Claim 1, wherein
said body of said commutator includes an annular recess and said magnetic ring is housed in and
adhesively bonded to said ~~an annular recess located on said body of said commutator, on which~~
~~said magnetic ring is adhesively bonded.~~
4. (CURRENTLY AMENDED) The motorized reduction gear as recited in Claim 1,
wherein said commutator includes an annular recess located at an end of said commutator, and
said magnetic ring is housed in ~~an~~ the said ~~annular recess located at an end of said commutator.~~

Serial No. 09/760,017
60130-984
OOMRA0174

5. (CURRENTLY AMENDED) A motorized reduction gear comprising:
a rotor provided with a rotor shaft bearing a commutator;
said commutator including an annular extension and a body having an inner surface
mounted on said rotor shaft and an opposing outer surface;
a reduction gearbox containing a gearwheel engaged with a worm of said rotor shaft; and
a magnetic ring mounted on said rotor shaft so that a number of rotations of said rotor
shaft can be counted~~The motorized reduction gear as recited in Claim 1, wherein said magnetic~~
~~ring is attached on said opposing outer surface of said body of said commutator and is elastically~~
~~clipped onto an said annular extension of said commutator.~~
6. (CURRENTLY AMENDED) The motorized reduction gear as recited in Claim 1, wherein
said commutator includes an end and an axis, and said magnetic ring is attached to one said end of
said commutator by at least two screws substantially parallel to an said axis of said commutator.
7. (CURRENTLY AMENDED) The motorized reduction gear as recited in Claim 1, wherein
said commutator includes a body having an annular recess, and said magnetic ring is housed in an
annular recess located on said body of said commutator, on which said magnetic ring is and
overmolded on said annular recess of said commutator.
8. (PREVIOUSLY PRESENTED) The motorized reduction gear as recited in claim 4,
wherein said end of said commutator is free of hooks.
9. (NEW) The motorized reduction gear as recited in claim 1, further including an
attachment feature that attaches said magnetic ring to said commutator.
10. (NEW) The motorized reduction gear as recited in claim 9, wherein said attachment
feature is a threaded member.
11. (NEW) The motorized reduction gear as recited in claim 9, wherein said attachment
feature is an elastic clip.

Serial No. 09/760,017
60130-984
00MRA0174

12. (NEW) The motorized reduction gear as recited in claim 9, wherein said attachment feature is an adhesive.